

High Plains Demolition Derby
Compact Car Rules/ Hobby Class Full Size Cars
CHAIN CLASSES

Car Rules

1. This is absolutely a no weld class of cars except what is permitted in the rules.
2. Radiator and cooling systems must remain in stock position.
3. Auxiliary water systems are not allowed. The original or an automobile radiator must be left in its original location. You may remove the fan if desired.
4. **DOORS:** All doors must be bolted or chained shut.
 - a. The Drivers door may be welded shut.
 - b. The driver's door may be reinforced on the inside and outside of the car. The inside of the door may be padded if DESIRED. The only restrictions to this rule, at present is: *As of 2006 All Cars must have a bar door post to door post behind the driver seat. No exceptions.*
 - c. *All Drivers doors must be painted Orange. Orange cars must paint the door yellow. A 3 sided Roof sign with your number on it is mandatory.*
 - (1) Any bar located in front of the driver for the purpose of reinforcing the driver's door may extend from drivers side door to passenger side door across the firewall. You may also;
 - a. Extend from drivers side door diagonally to passenger side frame. You can weld or bolt to frame.
 - b. Extend from drivers side door, parallel to the floor and not exceed 12 inches past the center of the car before it angles directly to passenger side frame. You can weld or bolt to frame.
 - c. A bar may be added to passenger side front and rear protection bars.
 - d. Only one front protection bar may be used. You may **not** go to both the frame and the door post.
 - (2) NO GRADER BLADES ON DOORS. Reinforcement to outside of door may only extend 6" past door seams of car toward the front and the back. Please taper all corners so as not to rip sheet metal on other cars. (Will be required by judges)
5. 2" to 4" pipe behind driver's seat. It must have a 6" minimum or 16" maximum plate welded on both ends and bolted or welded to the car. (For safety only no support members)
6. **FRAMES:** Homemade motor mounts, transmissions mounts, and rear-end mounts will be allowed to be welded to the frame.
 - a. Motor mounts can be welded to the frame but must be 4" in front or 4" behind the original motor mount.
7. **HOODS:** be bolted, strapped or chained down. (Can only pick two)
 1. **If bolted:** It may not be bolted in more than six (6) locations and the maximum size of material will not exceed (1) ½" ready rod (2) washer plate size must not exceed 4"X4" (3) No bolting of material will be allowed to be placed in front of the radiator for the purpose of protecting

the radiator. Addition for 2006.... ***ALL Cars will be required to have two bars or rods in the window to keep hood from coming in on the driver no exceptions.***

2. **If Strapped:** It may be strapped from hood to front bumper in only two locations and the maximum size of material to be used will not exceed 2" wide by 3/8" thick and no longer than it takes to reach from the hood to the bumper to be attached. No strapping material will be allowed to be placed directly in front of the radiator for the purpose of protecting the radiator. Straps can be bolted only.
3. **If Chained:** No more than two (2) single strand wraps will be allowed from the bumper to the hood. No chains will be allowed to be placed in front of the radiator. Chains can be bolted only.
- 7a. All hoods must be left in their original stock location. A hood may be bent over the front bumper provided the hood has not been slid forward.
- 7b. All hoods bolted, strapped, or chained will have to have two (2) fire extinguisher holes in the hood, one (1) on each side of the carburetor, a minimum of 6" in diameter.
- 7c. Hood may be folded to top of the fender only not down the side. This will be a judge's call. Use discretion when doing so or you will be made to cut it if the judges feel it is on the side of the fender. Hood may not be folded to cover the radiator of the car.

8. **TRUNKS:** All trunk lids must be bolted, strapped, or chained shut. Pick two.
 - a. **If Bolted:** It may not be bolted in more than four (4) locations and the maximum size material to be used will not exceed (1) 1/2" diameter ready rod (2) washer plate size must not exceed 4"X 4".
 - b. **If Strapped:** It may be strapped from the trunk lid to the rear bumper in only two(2) locations and the maximum size material to be used will not exceed 2" wide, 3/8" thick and no longer than it takes to reach from the bumper to the trunk to be attached.
 - c. **If Chained:** No more than two (2) single strand wraps will be allowed from bumper to the trunk.
9. **SUSPENSIONS: NO MODIFICATION** to the front or rear suspensions are allowed.
 - a. All shackles lift kits, and blocks must be removed.
 - b. No welded or modified shocks.
 - c. All air shocks must be cut.
 - d. No more than a total of 8 leaf spring clips will be allowed on the car.
 - (1) A maximum of 2 in front and 2 behind the rear differential on each side.
 - (2) These clips must be similar in size to the original if not the original stock clips.
 - e. The rear differential must sit on top of the leaf springs.
 - f. Exceptions
 - (1) Chains will be allowed to make repairs if, and only if, a ball joint has been broken.

- (2) You will be allowed to chain the rear-end to the body or frame.
- g. No welding on leaf springs will be allowed.
- h. The lower part of the strut up to 6" may be welded, but no added material is to be used for support other than welding wire or rod.
- i. **Cars must remain at stock height. Judges discretion applies.**
- 10. **BUMPERS:** Bumpers may be welded to a chain that is welded to the bumper only. No direct welding of the bumper to the frame.
 - a. Bumpers and bumper mounts can be changed. They must be off of a compact or sub-compact car and cannot be wider than the car.
 - b. A 5 X 5 plate (3/8" thick) may be welded to the bumper only.
 - c. Homemade bumper mounts to frame made of 3/8" metal can only be bolted up to 6" on frame.
- 11. Transmission coolers are allowed.
- 12. Any tire and tread. **NO STUDED TIRES.** You may protect valve stems.
- 13. Driver's door may be painted a contrasting color. This is your choice to do so.
- 14. You may weld washers to the cars body (4" maximum diameter) to run chains or wire through to prevent from tearing the sheet metal on the car.
- 15. **SCREWS:**
 - a. You may use screws up to 1/8" in size to screw the car together. There must be a 2" gap between screws.
 - b. You may use screws or bolts on the car to tie the sheet metal together.
 - (1) Screws or bolts larger than 1/4" in size and below 1/2" in size must have a 4" spacing between them.
- 16. All cars must have air cleaners.
- 17. All cars will be numbered on both sides in contrasting colors. Numbers must be at least 12" in height. A three sided roof sign is a must with the number on all three sides. **NO FLAGS.**

Compact Car Specifications and Regulations

1. Any stock compact car is allowed up to 2900lbs. **And up to 105" maximum wheel base.** Must be stated as which in NADA Blue Book.
2. No V8 engines, 4X4, pickups, or convertibles.
3. All glass must be removed from the car. That means ALL GLASS!! This includes fiber glass.

<ul style="list-style-type: none"> a. Windshields b. Rear windows c. Side windows d. Mirrors e. Headlights 	<ul style="list-style-type: none"> f. Tail-Lights, bulbs and lenses. g. turning lights, bulbs and lenses h. Back up lights, bulbs and lenses i. Items e-h includes all brackets and mounting assemblies that holds these lights in place.
---	---

4. All chrome molding strips and molding clips must be removed from the car. This includes the following.
 - a. Hood
 - b. Fenders
 - c. Sides of the vehicle
 - d. Trunk lid
5. The following items must be removed from the passenger compartment and trunk area:
 - a. All inside door panels
 - b. All carpeting and padding
 - c. The headliner
 - d. The rear seat
6. The original gas tank must be removed and a metal six (6) gallon maximum capacity tank must be securely fastened in front of the rear axle, inside the car. Tanks must be surrounded in a metal case if plastic or they must be metal no exceptions. If a car is seen as unsafe by the judges it will not run until it is deemed safe. It must not leak and must be properly ventilated. No Exceptions (boat tanks are highly recommended). Regular, Unleaded, Diesel, and Aviation fuel will be the only fuels allowed to be used. Six gallons will be MAXIMUM PERMITTED in the car at one time. NO EXOTIC FUELS PERMITTED!!! **All tanks must be covered with a non-absorbent cover such as a mud flap or inner tube to prevent the driver from being splashed with fuel.**
7. The original battery must be removed and one securely installed in the passenger side front floor board, a white rag tied to the positive battery cable and **battery must be covered.**
8. All trailer hitches, shackles, lift kits, and blocks must be removed. All air shock lines must be cut.

HOBBY CLASS AMENDMENTS.

1. NO IMPERIALS or IMPERIAL SUBFRAMES
2. 1" All Thread will be allowed
3. NO STUDDED or PADDLE TIRES ON DRIVE TIRES
4. BUMPERS MAY BE WELDED TO THE BRACKET AND THE BRACKET TO THE FRAME

ALL OF THE ABOVE RULES WILL BE STRICTLY ENFORCED

All contestants in the Derby are independent contractors. The Scottsbluff County Fair board or their representatives reserves the right to approve or reject any and all entries. The Scottsbluff County Fair board and anyone involved in promoting or participating in the event will not be held responsible for any cars, parts, or personal property before, during, and after the event.

**If you have any Questions feel Free to Call Eric Hardin
 (308) 436-3518
 Email: Playnfarmer@yahoo.com
 Jess Huss
 (308) 487-3737
 Email: jhuss@bbc.net**